

APPLICATION
FOR
UNITED STATES LETTERS PATENT

TITLE: Plug-and-Socket Connector Element
Claiming priority from the following:

Applicant claims priority on the following:

German Patent Application No. 100 36 890.5
filed July 28, 2000

German Utility Model No. 200 15 602.0
filed September 8, 2000

INVENTOR(S)

Marcus Cech
Ostfildern, Germany

Frank Andra
Deizisau, Germany

ASSIGNEE (if applicable)

Elektrische Bauelemente GmbH
Stuttgart, Germany

ENTITY: Large

Pierce Atwood
One Monument Square
Portland, ME 04101
207-791-1276

CERTIFICATE OF MAILING

"EXPRESS MAIL Mailing Label Number: EL469488924US Date of Deposit: July 24, 2001

I hereby certify under 37 CFR 1.10 that this correspondence is being deposited with the United States Postal Service as "Express Mail Post Office to Addressee" with sufficient postage on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, DC, 20231.

Constance S. Rogers

Constance S. Rogers

Plug-and-Socket Connector Element

BACKGROUND OF THE INVENTION

5 The invention relates to a plug-and-socket connector element with a connector base body, a connector fitting part, and at least one plug contact.

10 Conventional plug-and-socket connector systems comprise two complementary connector elements. One of the two connector elements is generally provided with plug contacts in the form of sockets, and the other connector element complementary therewith is provided with plug contacts in the form of pins.

15 During assembly of plug-and-socket connector elements, electric feed lines such as cables are connected to the plug contacts, for example via clamping screws which are arranged at the rear end of the plug contacts. The rear end of a plug contact is the end facing away from the complementary connector element.

20 Due to the fact that high voltages can be applied to the plug contacts it is generally necessary to provide predefined insulating air and creep paths for a certain rated voltage. For this reason, an insulation protection in the form of a fitting part is often provided for the plug contacts which are arranged in the base body of the connector element. The fitting part covers the rear ends of the plug contacts in such a manner that the required insulating air and creep paths are maintained.

25 Such fitting parts are often provided with latch elements which are employed for various purposes. The latch elements, for example, permit the coupling of the fitting part with the

base body or of a first connector element with a complementary second connector element. It is also possible to couple by means of the latch elements one of the connector elements with a support rail for the connector system.

German Utility Model DE GM 93 11 457 describes plug-and-socket connector fitting parts which are connected with opposite faces of a connector element by means of screws. The fitting parts each have a side wall extending in parallel to the faces of the connector element as well as a movable latch element in the form of a latch hook. The latch hook is arranged at an outer end of a lever arm which is part of a two-arm lever. The lever is pivotably coupled with the side wall via a web which extends radially outwards with respect to the plug-in direction of the connector element. The latch hook is connected to the side wall of the fitting part via the lever arm and the web.

The object underlying the invention is to provide a plug-and-socket connector system which permits a simple connection of the electric feed lines, is easy to handle, and which, beyond that, ensures a protection and, in particular, a reliable electric insulation of the rear ends of the plug contacts.

SUMMARY OF THE INVENTION

This object is solved by a plug-and-socket connector element with a base body in which at least one plug contact is arranged, wherein the plug contact permits the insertion of an electric feed line in an axial direction from the rear end of the at least one plug contact. The plug-and-socket connector element moreover comprises a fitting part which is movable with respect to the base body and can preferably be snapped onto the base body, the fitting part permitting a lateral access to the rear end of the at least one plug contact in a

first latch position and, in a second latch position, laterally covers the plug contact at least partially. The plug contact can, for example, be covered in the second latch position by a circumferential side wall or a side wall provided with openings. The side wall can be made from an insulating material. The fitting part is preferably brought from the first into the second latch position by an axial displacement or, alternatively, by a rotating movement.

The inventive connector element ensures a particularly simple connecting of the electric feed lines to the plug contacts in that the feed lines are inserted from the rear end of the plug contacts into same. In the first latch position (assembly position) the lateral access to the at least one plug contact enables to secure the feed lines at the plug contacts, e.g. by means of clamping screws or soldering. After securing of the electric feed lines, the fitting part is brought into the second latch position (work position) with respect to the base body. In the work position, the fitting part laterally covers the plug contacts at least partially so that the connection between each plug contact and feed line is protected, for example, against mechanical damage or an inadvertent disconnection.

Preferably, at least the portion of the fitting part covering the rear end of the plug contacts consists of an insulating material such as plastic. The base body can also consist of an insulating material. By manufacturing at least the portion of the fitting part covering the rear end of the plug contacts of an insulating material, insulating air and creep paths can be maintained, if required.

Due to the fact that the fitting part is in a latch position both in the assembly position and in the work position, it is ensured that the fitting part does not interfere with the

assembly of the electric feed lines through an inadvertent displacement. It is further ensured that the fitting part in the work position reliably covers the one or more plug contacts. Preferably, the fitting part is designed in such a manner that it can optionally be brought from the assembly position into the work position and vice versa.

An inventive connector fitting part has a side wall and at least one latch element connected with the side wall, wherein the side wall of the fitting part comprises one or several expandable areas which are connected with one or more latch elements each. Due to the connection of the latch element with the movable expandable area of the side wall, a latching connection between the fitting part and another component (e.g. the base body) having a complementary latch element can be realized in an easy manner.

The latch element can be formed as one piece with the expandable area, i.e. can be integrated in the expandable area, or it can be arranged as a separate component on the expandable area. The integration of the latch element via the expandable area into the side wall allows a reduction of the material costs compared to a fitting part at whose side wall a separate lever carrying the latch element is arranged by means of e.g. a web.

The expandable area preferably has resilient properties so that after an actuation, the latch element attempts to return into its initial position. In lieu of designing the expandable area itself so as to be resilient, it is also conceivable to provide separate resilient means which move the expandable area, and thus the latch element, after an actuation back into the initial position.

According to a preferred embodiment of the invention, the expandability of the resilient or not resilient, expandable area is realized by one or several folds of the expandable area. Thus, the expandable area can be designed similar to a bellows.

The latch element which is preferably surrounded at least on two sides or completely by the expandable area can be designed as a latch hook, a latch projection, or a latch recess. It is, for example, conceivable to design the latch element as a latch hook which, for the purpose of forming a latching connection, engages behind a corresponding latch projection or into a corresponding latch recess.

The latch element is preferably movable in a radial direction with respect to a longitudinal axis of the fitting part. An actuation mechanism can be provided for the latch element, which, for example, actuates the latch element due to a pressure acting on the actuation mechanism. According to a preferred embodiment, the actuation mechanism comprises an actuation lever with a first lever arm, the latch element being connected with said first lever arm. The first lever arm can be integrated at least almost completely in the expandable area. The lever arm is then part of the side wall of the fitting part.

The actuation lever can comprise a second lever arm which, at least partially, protrudes off the side wall. For operating the actuation mechanism, a force may be introduced into a section of the second lever arm protruding off the side wall. Thus, a pivoting movement of the latch element is effected. The actuation mechanism is preferably designed in such a manner that it allows a movement of the latch element in a radially outward direction with respect to the plug-in direction.

In order to prevent an inadvertent disconnection of the plug contacts from the base body, the fitting part may be provided with at least one extension which extends in an axial direction towards the base body. Said extension, which can be arranged between the side faces of the fitting part, cooperates with a plug contact in such a manner that the extension in the first latch position locks the plug contact axially displaceably against falling out, and in the second latch position locates the plug contact in an axially non-displaceable manner in the base body. Additionally or alternatively it is conceivable to secure such plug contacts, which may be arranged in respective chambers of the base body, by means of bulges in the chambers against becoming lost.

According to another embodiment of the invention, the fitting part is movable in a guided manner in an axial direction with respect to the base body. For this purpose, the fitting part or the base body is provided with a guide groove extending e.g. in an axial direction, and the base body or the fitting part has a corresponding projection which is guided in the guide groove. In addition, the fitting part can be captively connected with the base body. To achieve this, the guide groove, for example, is limited at opposite ends by means of corresponding stops for the guided projection.

In order to secure the feed lines at the plug contacts, the plug contacts are preferably provided with clamping screws in the area of the rear side of the plug contacts. These clamping screws can extend in a radial direction with respect to the axial extension of each of the plug contacts. The connector element can be designed both as a round and a rectangular connector element. According to a particularly preferred embodiment of the invention, the connector element is a standardized H-A 3 or H-A 4 insert. A preferred connector

element has at least two, and preferably at least four plug contacts. Each plug contact can be adapted for cable connection cross sections of 0.5 to 2.5 mm. In addition, the connector element can be provided with a ground connection.

DESCRIPTION OF THE DRAWINGS

Further advantages and details of the invention will become apparent from the following embodiments and the figures, in which:

- Fig. 1 shows a first embodiment of an inventive plug-and-socket connector element prior to the assembly of base body and inventive connector fitting part;
- Fig. 2 shows the connector element according to Fig. 1 in a first latch position (assembly position);
- Fig. 3 shows the connector element according to Fig. 1 in a second latch position (work position); and
- Fig. 4 shows a second embodiment of an inventive plug-and-socket connector element in the work position with the feed cables connected.

DESCRIPTION OF PREFERRED EMBODIMENTS

Fig. 1 illustrates a first embodiment of an inventive plug-and-socket connector element 10 in the form of an H-A 3 socket insert. The connector element 10 comprises a two-part insulating body 12, 14 consisting of a base body 12 and an inventive connector fitting part 14. Both the base body 12 as well as the fitting part 14 are completely made from plastic.

The base body 12 is designed for the accommodation of four socket plug contacts 16 and one ground connection 18. Fig. 1 shows three plug contacts 16 of the altogether four plug contacts 16. Each of the plug contacts 16 is provided at its rear end with a clamping screw 20 for the securing of cables.

The plug contacts 16 are inserted into contact chambers, which are not shown in Fig. 1, of the base body 12. In the illustration according to Fig. 1, a first of the plug contacts 16 has not yet been inserted, a second of the plug contacts 16 has been inserted halfway, and a third of the plug contacts 16 has been fully inserted into the respective contact chamber. The ground connection 18, which comprises two sections extending towards each other at right angles, can be inserted into a guide groove 22 of the base body 12. The guide groove 22 extends in an axial direction. The section of the ground connection 18 which extends vertically to a longitudinal axis A of the connector element 10 comes to rest against the rear end surface of one of the plug contacts 16. Consequently, this plug contact 16 acts as a ground contact.

In order to enable snapping-on of the fitting part 14 on the base body 12, two opposite rear side walls of the base body 12 are provided with two latch recesses 24 and 26 each, which are offset in an axial direction. Fig. 1 shows only one of the side faces of the base body 12 with the latch recesses 24 and 26.

Another guide groove extending in an axial direction is formed on that rear side face of the base body 12, which is located opposite the side face comprising the guide groove 22 for the ground connection 18 and which is not shown in Fig. 1. This further guide groove is terminated at its two axial ends by one stop each which extends vertically to the longitudinal axis A.

The fitting part 14 of the connector element 10 shown in Fig. 1 comprises a side wall 30 which extends towards the base body 12 in an axial direction. This side wall 30, however, is not designed so as to be fully circumferential, but has an opening 32 for enabling a lateral access to the ground connection 18 also in the work position of the fitting part 14 with respect to the base body 12.

A guide pin 34 is arranged in the center of the fitting part 14 and extends towards the base body 12 in an axial direction. This guide pin 34 has an asymmetric cross section. Upon snapping on of the fitting part 14 the guide pin 34 cooperates with a corresponding opening of the base body 12. The opening has a corresponding cross section and extends in an axial direction, in order to enable a snapping-on of the fitting part 14 on the base body 12 in the correct position.

On its side opposite the opening 32, the side wall 30 of the fitting part 14 comprises a projection 36 in the form of a latch hook which protrudes from the plane of the drawing. This projection 36 cooperates with that guide groove of the base body 12 which is not shown in Fig. 1 and located opposite the guide groove 22. The projection 36 of the fitting part 14 and the corresponding guide groove of the base body 12 ensure, on the one hand, that the fitting part 14 is captively connected with the base body 12 and, on the other hand, a reliable axial guidance of the fitting part 14 on the base body 12 between the two possible latch positions.

In addition, the fitting part 14 is provided with one extension 38 each for each plug contact 16. The extension 38 extends towards the base body 12 in an axial direction. Fig. 1 shows only one of the altogether four extensions 38. Each of the extensions 38 cooperates with the corresponding plug

contact 16 and, in the assembly position of the fitting part 14, limits the axial movability of each of the plug contacts 16. In the work position of the fitting part 14, each of the plug contacts 16 is held in an axially immovable manner in the base body 12 by these extensions 38.

The fitting part 14 comprises two actuation levers 40 and 42. These actuation levers 40 and 42 are formed at opposite side faces of the fitting part 14. Due to the fact that the two actuation levers 40 and 42 are designed identical, in the following the actuation lever 40 will be described in more detail by way of example.

The actuation lever 40 comprises a first lever arm in the form of an actuation arm 44 which extends away from the base body 12 in an axial direction, as well as a second lever arm 46 which extends towards the base body 12 in an axial direction. The two lever arms 44 and 46 are connected with each other and with the fitting part 14 via a web 48 which extends vertically to the longitudinal axis A of the connector element 10.

At its end facing towards the base body 12, the lever arm 46 is provided, with respect to the longitudinal axis A of the connector element 10 radially on its inside, with a latch element. The latch element is a latch hook 50 extending towards the longitudinal axis A. This latch hook 50 cooperates with the two latch recesses 24 and 26 of the corresponding side wall of the base body 12.

The lever arm 46 provided with the latch hook 50 is integrated in the side wall 30 of the base body 12 via one expandable area 52 and 54 each. The expandable areas 52 and 54 are designed in a bellows-type manner and therefore, through the operation of the actuation lever 40, allow a movement of the latch hook 50 formed at the lever arm 46 with respect to the

longitudinal axis A in a radial direction and outwardly against the restoring force generated by the expandable areas 52 and 54.

5 The fitting part 14 comprising the side wall 30, the expandable areas 52 and 54, and the actuation levers 40 and 42 is designed as an integral component and can therefore be manufactured extremely easily and economically. The thickness of the side wall 30 in the region of the lever arm 46 is greater than that of the expandable areas 52 and 54 or of the other regions of the side wall 30. The thickness of the side wall 30 is preferably lowest in the region of the expandable areas 52 and 54.

10
15 In order to ensure an ergonomically easy actuation of the actuation lever 40, the lever arm 44 which extends away from the base body 12 in an axial direction is provided with an actuation surface 56. This actuation surface 56 lies in the plane defined by the expandable areas 52, 54 and the lever arm 46. Like the lever arm 44, the actuation surface 56 projects beyond the side face 30.

20
25 In the delivery condition of the connector element 10 of Fig. 1, the fitting part 14 is snapped on the base body 12 in such a manner that a latch connection is made between the latch hook 50 of the actuation lever 40 and the latch recess 24 of the base body 12. The latch hook of the actuation lever 42 also makes a corresponding latch connection with the base body 12. In addition, the projection 36 of the fitting part 14 is located in the corresponding guide groove of the base body 12. This first latch position (assembly position) of the fitting part 14 with respect to the base body 12 is shown in Fig. 2.

30
35 In the assembly position of the fitting part 14 with respect to the base body 12 shown in Fig. 2, the fitting part 14 per-

mits a lateral access to the clamping screws 20. From the rear end of the plug contact 16, i.e. from the right side in Fig. 2, cables with or without conductor end sleeve can be inserted into the plug contacts 16 which are designed as clamping contacts. Following the insertion of the cables, these are connected with the plug contacts 16 by means of the clamping screws 20.

After fastening the cables, the fitting part 14 of the connector element 10 is moved towards the base body 12, i.e. to the left side in Fig. 2, until the latch hooks of the actuation levers 40, 42 engage the respective second latch recesses. This corresponds to the work position of the connector element 10 shown in Fig. 3.

As can be seen from Fig. 3, the plug contacts 16 shown in Fig. 2 are completely covered by the side wall 30 of the fitting part 14. The expandable areas 52 and 54 of the side wall 30 of the fitting part 14 also contribute to the covering of the plug contacts 16 depicted in Fig. 2. In the work position shown in Fig. 3, the plug contacts 16 are reliably protected against mechanical damage and, in particular, against inadvertent opening. In addition, the side wall 30 made of an insulating material ensures that specified air and creep paths for a given rated voltage are maintained. The fitting part 14 therefore acts as an insulating cap.

The latch connection between the latch hooks of the two actuation levers 40 and 42 and the corresponding latch recesses of the base body 12 is disconnected by pressing onto the actuation arms of the two actuation levers 40 and 42 towards the longitudinal axis A of the connector element 10. Consequently, after an operation of the two actuation levers 40 and 42, the fitting part 14 can be moved from the work position shown in Fig. 3 again into the assembly condition shown in Fig. 2 by

means of an axial displacement away from the base body 12, i.e. to the right side in Fig. 3 (reversibility).

Fig. 4 shows a second embodiment of an inventive plug-and-socket connector element 10 in the form of an H-A 4 insert in the work position. The H-A 4 insert according to Fig. 4 has one more working contact than the H-A 3 insert of Figs. 1 to 3 and consequently comprises four working contacts and one ground contact. Otherwise, the H-A 4 insert of Fig. 4 corresponds to the H-A 3 insert of Figs. 1 to 3.

The connector element 10 according to Fig. 4 has four socket plug contacts in the form of working contacts. One cable 62 each is connected with each of these four working contacts. In addition, the connector 10 according to Fig. 4 has a fifth socket plug contact at which a protective conductor cable 68 is connected.

Whereas the three working contacts as well as the ground contact of the connector element shown in Figs. 1 to 3 are all assembled in the assembly position shown in Fig. 2, only the four working contacts of the connector element shown in Fig. 4 are assembled in the assembly position. The assembly of the protective conductor contact is made in the work position shown in Fig. 4. The connector elements 10 shown in Figs. 1 to 4 can be mounted in standard housings H-A 3 and H-A 4.

The inventive fitting parts explained with reference to Figs. 1 to 4 are components for covering the base body 12 accommodating the plug contacts 16 of a two-piece plug-and-socket connector element in an electrically isolating matter. It goes without saying that the inventive connector fitting part can also be employed for other purposes in the context of a connector system. It is conceivable to provide two complementary connector elements and to secure an inventive

connector fitting part at each of these connector elements in order to captively couple the two complementary connector elements by means of the two complementary connector fitting parts. An inventive fitting part which is secured at a connector element can also be used to couple the connector element, for example, with a support rail for a connector system. Furthermore, it is possible to form the inventive fitting part integrally with the connector element accommodating the plug contacts. In the sense of the invention, this case would relate to a fitting part with respect to the plug contacts.

5

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212